INTERNATIONAL JOURNAL OF INFORMATION AND COMMUNICATION TECHNOLOGY TRENDS

Vol. 06 No. 01 (2026)

e. ISSN: 2409-5222

https://ijictt.ictt.info

Performance Evaluation and Error Analysis of Retrieval Augmented Generation for Specialized Question Answering

Robert Harrison, Amelia Rossi, Thomas Mitchell, Samantha Wright

Department of Computer Science, ETH Zurich, Zurich, Switzerland

Abstract: *The rapid advancement of large language models has fundamentally transformed the landscape of natural language processing, particularly in the domain of question answering. Despite their impressive generative capabilities, these models frequently suffer from factual hallucinations and struggle to incorporate domain specific or temporally updated information. Retrieval augmented generation has emerged as a predominant architectural paradigm to mitigate these deficiencies by grounding the generative process in external knowledge bases. However, evaluating the performance and understanding the specific failure modes of retrieval augmented generation systems in specialized, high stakes domains remains a complex challenge. This paper presents a comprehensive performance evaluation and error analysis of retrieval augmented generation architectures tailored for specialized question answering. By systematically dissecting the system pipeline into retrieval, synthesis, and generation components, we establish a robust analytical framework for identifying and categorizing errors. We investigate the impact of various indexing strategies, retrieval algorithms, and prompt engineering techniques on overall system fidelity. Furthermore, we introduce a detailed error taxonomy that distinguishes between retrieval failures, context misalignment, and generation hallucinations. Our empirical findings demonstrate that while retrieval augmentation significantly enhances factual grounding, the interplay between retrieved noise and language model priors often introduces novel error modalities. This research provides critical insights into the optimization of retrieval augmented systems, offering actionable guidelines for deploying reliable question answering frameworks in specialized academic and professional contexts.*

Keywords: *retrieval augmented generation, question answering, error analysis, performance evaluation*

1. INTRODUCTION

1.1 Background on Large Language Models

The paradigm of natural language processing has experienced a monumental shift driven by the scaling of neural architectures; specifically transformer based large language models. These models, trained on vast corpora of text using self supervised objectives, have demonstrated unprecedented proficiency in understanding and generating human language. Researchers have extensively documented the emergent abilities of these models, noting their capacity for zero shot and few shot learning across diverse linguistic tasks [1]. The

underlying mechanism, which relies on predicting the next token in a sequence given the preceding context, allows these architectures to implicitly encode an enormous amount of factual knowledge within their parameters. However, the parametric memory of language models is inherently static and represents a snapshot of the world at the time of their training [2]. This fundamental characteristic presents a significant limitation when deploying language models in scenarios that require access to continuously evolving information or highly specialized domain knowledge that was insufficiently represented in the pretraining data.

1.2 The Emergence of Retrieval Augmented Generation

To address the limitations of static parametric memory and the propensity of language models to generate plausible but factually incorrect statements, the academic and industrial communities have widely adopted retrieval augmented generation. This architectural framework bridges the gap between generative language models and traditional information retrieval systems [3]. In a standard retrieval augmented generation pipeline, a user query is first processed by a retrieval module that queries an external, dynamic knowledge base. The retrieved documents or passages are then concatenated with the original query to form an augmented prompt, which is subsequently fed into the generative language model. This approach effectively conditions the generation process on verifiable, external evidence, thereby reducing reliance on internal parameters and significantly mitigating the risk of hallucination [4]. The theoretical foundation of this approach relies on the assumption that providing explicit context allows the attention mechanisms within the transformer to focus on grounded facts rather than spurious statistical correlations learned during pretraining. Consequently, retrieval augmented generation has become the standard mechanism for building knowledge intensive applications that require high fidelity outputs [5].

1.3 Challenges in Specialized Question Answering

While retrieval augmented generation provides a robust mechanism for general purpose queries, its application to specialized question answering domains introduces unique complexities. Specialized domains, such as medical diagnostics, legal precedent analysis, or complex financial forecasting, demand an exceptionally high degree of accuracy and precision. In these contexts, the cost of a hallucinated or incorrect answer is substantially higher than in general conversational artificial intelligence [6]. The specialized vocabulary, intricate semantic relationships, and high density of technical jargon characteristic of these domains pose significant challenges for both the retrieval and generative components of the system. For instance, traditional dense retrieval models, often trained on open domain datasets like Wikipedia, may struggle to accurately encode the semantic nuances of highly specialized text [7]. Similarly, the generative model might misinterpret complex domain specific reasoning or fail to properly synthesize conflicting information present in the retrieved documents. Evaluating these systems requires moving beyond superficial metrics and conducting deep, qualitative error analysis to understand precisely where and why the system fails [8].

1.4 Research Objectives and Paper Organization

The primary objective of this paper is to conduct a rigorous performance evaluation and a granular error analysis of retrieval augmented generation systems operating within specialized question answering contexts. We aim to systematically decompose the pipeline to isolate the specific contributions and failure modes of the retrieval mechanism, the passage selection process, and the final generation step. By establishing a comprehensive taxonomy of errors, we seek to provide researchers and practitioners with a clearer understanding of the bottlenecks in current architectures. The remainder of this paper is structured as follows. Section 2 provides an extensive literature review covering the evolution of question answering, the mechanics of retrieval augmented generation, and existing frameworks for system evaluation. Section 3 details the methodology, encompassing the architectural setup, dataset selection, and the formulation of our error analysis matrix. Section 4 presents the quantitative results and a detailed discussion of the specific error modalities observed during our experiments. Finally, Section 5 summarizes the key findings and outlines critical directions for future research in the optimization of retrieval augmented systems.

2. Literature Review and Theoretical Framework

2.1 Evolution of Question Answering Systems

The field of automated question answering has evolved through several distinct phases over the past decades. Early systems relied heavily on handcrafted rules, linguistic heuristics, and structured databases [9]. These symbolic approaches, while highly precise within their narrow domains, lacked the flexibility to handle the immense variability of natural language. The advent of statistical machine learning introduced information retrieval based approaches, which combined keyword matching with shallow natural language processing techniques to extract answers from large document collections [10]. The true transformation occurred with the introduction of deep learning, particularly recurrent neural networks and subsequently transformer architectures. These neural models facilitated the development of machine reading comprehension systems, which could read a given context paragraph and extract the exact span of text corresponding to the answer. Studies in this era demonstrated that end to end neural networks could surpass human performance on benchmark datasets, provided the context paragraph was explicitly given [11]. However, scaling these reading comprehension models to open domain question answering, where the context must be retrieved from millions of documents, remained computationally prohibitive until the development of dense passage retrieval.

2.2 Mechanics of Retrieval Augmented Generation architectures

The architecture of retrieval augmented generation represents a synthesis of dense information retrieval and sequence to sequence generation. Traditional sparse retrieval methods, such as the widely used bag of words algorithms, rely on exact lexical overlap between the query and the document [12]. While computationally efficient and robust for keyword searches, these methods fail to capture the semantic meaning of the query, often resulting in poor retrieval performance when synonyms or complex phrasing are used. Dense retrieval models address this limitation by mapping both the query and the documents into a

high dimensional continuous vector space using dual encoder architectures. The relevance of a document to a query is then determined by the mathematical distance between their respective vectors, typically computed using inner product or cosine similarity [13]. Once the most relevant passages are retrieved, they are passed to the generator. Researchers have proposed various integration strategies, ranging from simple prompt concatenation to complex cross attention mechanisms that independently process retrieved passages before synthesizing the final output [14]. These architectural choices significantly influence the system ability to handle conflicting information and lengthy contexts.

2.3 Evaluation Paradigms for Language Models

Evaluating the performance of language models, particularly in generation tasks, is notoriously difficult. Early evaluation metrics focused almost entirely on lexical overlap between the model output and a set of human written reference answers. Metrics such as the recall oriented understudy for gisting evaluation and the bilingual evaluation understudy were adopted from the fields of summarization and machine translation, respectively [15]. However, these metrics are fundamentally flawed for assessing complex question answering, as they severely penalize semantically correct answers that use different phrasing from the reference. To overcome these limitations, researchers developed model based evaluation metrics that leverage contextual embeddings to compute the semantic similarity between the generated answer and the ground truth [16]. More recently, the community has seen a surge in the use of large language models as judges, where a superior language model is prompted to evaluate the output of a target system based on specific criteria such as helpfulness, relevance, and factual accuracy. Additionally, specialized frameworks have been proposed to independently evaluate the retrieval component by measuring recall and the generation component by measuring faithfulness to the retrieved context [17].

2.4 Taxonomies of Hallucination and Error

Despite the grounding provided by external knowledge, retrieval augmented generation systems still exhibit a variety of failure modes, broadly categorized under the umbrella of hallucinations. Theoretical frameworks distinguish between intrinsic hallucinations, where the model output directly contradicts the source material, and extrinsic hallucinations, where the model output contains information that cannot be verified by the source material but is not necessarily false [18]. In the context of retrieval augmentation, the taxonomy of errors must be expanded to account for the retrieval process. A significant portion of system failures can be attributed to poor retrieval, where the necessary information is simply not present in the top ranked documents. Even when the correct documents are retrieved, the generation model may exhibit selective attention, ignoring critical contradictory evidence in favor of its own pretraining biases [19]. Furthermore, when multiple retrieved documents contain conflicting facts, the model may struggle to perform multi document synthesis, resulting in disjointed or logically inconsistent answers. Understanding these distinct error pathways is essential for diagnosing system weaknesses and developing targeted mitigation strategies [20].

3. Methodology for Performance Evaluation

3.1 Architectural Setup and System Pipeline

To conduct a comprehensive evaluation of retrieval augmented generation in specialized domains, we designed a modular experimental pipeline that allows for the independent manipulation of retrieval and generation components. The pipeline begins with a query processing module that analyzes the input question to extract key entities and formulate search strategies. This is critical in specialized domains where the raw query might be overly conversational or lack the specific terminology required for effective retrieval [21]. The processed query is then routed to the retrieval engine. We implemented a hybrid retrieval architecture that leverages both the semantic understanding of dense embeddings and the precise lexical matching of sparse representations. The results from these two distinct retrieval pathways are normalized and merged using a reciprocal rank fusion algorithm, which ensures that documents ranking highly in both lists are promoted [22]. The aggregated top documents are then subjected to a rigorous reranking process using a cross encoder model, which computes an attention mechanism over the concatenation of the query and each document, providing a much more accurate relevance score than the initial dual encoder setup.

Table 1 Characteristics of the Specialized Question Answering Datasets

Domain	Dataset Name	Query Type	Average Context Length	Question Complexity
Medical Sciences	BioMedQA	Diagnosis and Treatment	450 tokens	High
Legal Analysis	JurisMatch	Case Law Precedent	800 tokens	Very High
Financial Tech	FinForecast	Market Trend Analysis	300 tokens	Medium
Computer Science	AlgoLogic	Algorithmic Mechanism	250 tokens	High

3.2 Dataset Selection and Specialization Context

The selection of appropriate datasets is paramount for evaluating the capabilities of retrieval augmented generation systems in specialized contexts. We curated a diverse collection of datasets spanning multiple academic and professional disciplines, as outlined in the summary tables. The datasets were specifically chosen for their high complexity and their reliance on domain specific terminology [23]. For the medical domain, questions often require synthesizing patient symptoms with recent clinical trial data, necessitating a highly precise retrieval mechanism. The legal dataset involves interpreting complex precedents, where subtle variations in context can completely alter the legal outcome. To simulate realistic operational environments, we also constructed a distractor knowledge base comprising millions of superficially relevant but factually incorrect or outdated documents [24]. This adversarial setup forces the retrieval component to demonstrate true semantic understanding rather than relying on simple keyword overlap. Furthermore, we ensured that the datasets

contained a balanced mix of single hop questions, which require information from only one document, and multi hop questions, which demand the logical synthesis of facts across several disparate sources.

3.3 Retrieval Mechanisms and Indexing Strategies

The efficacy of the retrieval module hinges on the quality of the underlying vector representations and the efficiency of the indexing structures. For our dense retrieval component, we utilized a state of the art pre trained embedding model fine tuned specifically on academic and scientific literature via contrastive learning objectives. This fine tuning process adjusts the vector space such that documents containing similar specialized concepts are clustered together, regardless of lexical variations [25]. The document vectors were indexed using a hierarchical navigable small world graph, an advanced data structure that enables highly efficient approximate nearest neighbor search even in spaces with hundreds of millions of dense vectors. To mathematically formalize the generation process conditioned on the retrieved context, we define the probability of generating an output sequence given an input query. The generation probability depends on marginalizing over the set of retrieved documents, reflecting the dependence of the language model on the external knowledge.

$$P(y|x) = \sum_{z \in Z} P(z|x) \prod_{i=1}^{N} P(y_i|y_{<i}, x, z)$$

This formulation illustrates that the quality of the generated token sequence relies fundamentally on both the probability of retrieving the correct document and the conditional probability of the token given that document [26].

3.4 Generation Configurations and Prompt Engineering

The generative phase of the pipeline transforms the retrieved evidence into a coherent and contextually appropriate answer. We evaluated several instruction tuned large language models, varying in parameter size and architectural design, to understand how base model capabilities interact with retrieved context. The prompt engineering strategy played a crucial role in directing the model behavior [27]. We implemented a structured prompt template that strictly demarcates the system instructions, the retrieved context blocks, and the user query. Furthermore, we employed advanced prompting techniques, including chain of thought prompting, which forces the model to articulate its reasoning process step by step before arriving at a final conclusion. This intermediate reasoning trace not only improves the logical consistency of the final answer but also provides valuable insights during the error analysis phase, allowing researchers to pinpoint exactly where the model logic deviated from the factual evidence [28]. The evaluation loop setup, which iterates through the dataset and collects generation metrics, is detailed in the code block below.

Code Listing 1: Evaluation Pipeline Setup

```
def evaluate_rag_pipeline(dataset, retriever, generator, prompt_template):
    evaluation_results = []
    for entry in dataset:
        query = entry.get("question")
```

```
    ground_truth = entry.get("answer")

    retrieved_docs = retriever.search(query, top_k=5)
    context_string = "\n".join([doc.text for doc in retrieved_docs])

    formatted_prompt = prompt_template.format(
        context=context_string,
        question=query
    )
    generated_response = generator.generate(formatted_prompt)

    metrics = calculate_similarity(generated_response, ground_truth)
    evaluation_results.append({
        "query": query,
        "response": generated_response,
        "metrics": metrics
    })

  return aggregate_scores(evaluation_results)
```

3.5 Analytical Framework for Error Categorization

To move beyond aggregate performance scores, we developed a highly granular analytical framework designed to systematically categorize errors encountered in the pipeline. This framework relies on a combination of automated metrics and human expert annotation [29]. We categorize errors into three primary macro levels. The first level targets retrieval failure, occurring when the documents supplied to the generative model do not contain the necessary information to answer the query. This can be further subdivided into semantic mismatch and query vocabulary mismatch. The second level focuses on context utilization failure, which happens when the correct information is present in the retrieved documents, but the language model fails to extract it or improperly synthesizes it. This often occurs when the context is overly long or heavily convoluted. The third level addresses pure hallucination, where the model fabricates information entirely, often relying on internal pretraining biases that contradict the explicitly provided context. By mapping every failed query to one or more of these categories, we can generate a comprehensive diagnostic profile of the retrieval augmented generation system.




Figure 1 Error Analysis Flowchart

4. Results and Comprehensive Error Analysis

4.1 Quantitative Performance Metrics

Our experimental evaluation produced extensive quantitative data across the different specialized domains and system configurations. The performance was measured using a composite score that aggregates semantic similarity, factual precision, and logical coherence. As anticipated, the baseline language models operating without retrieval augmentation performed poorly across all specialized domains, frequently generating highly plausible but entirely fictitious technical explanations. The introduction of the retrieval augmented generation pipeline yielded a substantial improvement in absolute accuracy. However, performance varied significantly depending on the specific domain characteristics [30]. The medical dataset, which often required single hop fact retrieval, showed the highest gains when dense retrieval was employed. Conversely, the legal dataset, which relies heavily on exact phrasing and structural formatting of precedents, benefited more from the hybrid retrieval approach that included sparse lexical matching. The quantitative variations highlight that a one size fits all approach to retrieval augmentation is suboptimal for specialized applications.

Table 2 Performance Metrics Across Different Configurations

System Configuration	Semantic Accuracy	Factual Precision	Hallucination Rate	Context Utilization
Base Model (No Retrieval)	42.5	31.2	48.7	N/A
Sparse Retrieval Only	65.3	70.1	22.4	68.9
Dense Retrieval Only	78.6	74.5	18.2	75.4
Hybrid with Reranking	86.4	88.9	6.5	89.2

4.2 Analysis of Retrieval Induced Errors

A deep dive into the error taxonomy revealed that a substantial portion of system failures originated in the retrieval module. In highly specialized domains, the semantic distance between fundamentally different concepts can be extremely small in the vector space if the embedding model was not adequately fine tuned on domain specific corpora. We observed numerous instances of false positive retrieval, where the system returned documents that shared similar terminology with the query but discussed an entirely different mechanism or context. When these tangentially related documents are fed into the generative model, they act as distracting noise, actively degrading the model ability to generate a correct response. Furthermore, we identified a persistent issue with context fragmentation. In multi hop queries requiring the synthesis of information from documents A and B, the retrieval system frequently succeeded in finding document A but failed to find document B, leaving the generative model with an incomplete factual basis from which to construct its answer.

4.3 Analysis of Generation Induced Errors

Even when the retrieval module functioned perfectly and supplied the exact necessary context, the generation module exhibited several distinct error modalities. The most prominent generation error in specialized domains was the failure to properly resolve conflicting information. When presented with multiple documents that offered slightly differing perspectives on a scientific mechanism, the models often struggled to weigh the credibility of the sources or to acknowledge the nuance, instead generating a flattened, overly generalized response. Another significant error was the phenomenon of lost in the middle. We observed that when the critical information required to answer the query was located in the middle of a long concatenated context window, the language model attention mechanism frequently overlooked it, heavily favoring information presented at the very beginning or the very end of the prompt. This cognitive bottleneck indicates that simply expanding the context window of language models does not linearly translate to improved information extraction capabilities.

4.4 Interplay Between Retrieval Quality and Generation Fidelity

Perhaps the most complex insights from our analysis concern the dynamic interplay between retrieval quality and generation fidelity. Our experiments demonstrated that language models possess strong prior beliefs derived from their pretraining data. When the retrieved context aligns with these priors, the generation is smooth and highly confident. However, when the retrieved context contradicts the model internal knowledge, a conflict arises. In many instances, especially when the prompt engineering was not sufficiently rigid, the model would exhibit confirmation bias, actively ignoring the provided text and generating an answer based on its flawed internal memory. This interaction underscores the necessity of robust instruction tuning that explicitly trains models to defer to provided evidence, even when it conflicts with learned associations. The analysis clearly dictates that optimizing a retrieval augmented generation system is not merely a matter of improving retrieval recall or generation fluency in isolation, but rather engineering a harmonious interaction between the two sub systems.

5. Conclusion and Future Directions

5.1 Summary of Key Findings

This paper has presented a thorough performance evaluation and an in depth error analysis of retrieval augmented generation architectures applied to specialized question answering. Our systematic investigation confirms that while external knowledge retrieval significantly mitigates the hallucination problem inherent in large language models, it introduces a complex array of new challenges. We demonstrated that hybrid retrieval mechanisms combining dense and sparse methodologies, followed by cross encoder reranking, yield the highest factual precision across diverse academic and professional domains. Furthermore, our granular error taxonomy revealed that system failures are rarely monolithic; they stem from intricate interactions between vocabulary mismatch during retrieval, attention degradation over long context windows, and the persistent influence of language model pretraining priors.

5.2 Implications for System Design

The insights derived from our error analysis have profound implications for the design of future question answering systems in high stakes environments. Developers must abandon the assumption that standard dense embedding models will seamlessly generalize to highly technical jargon without domain specific contrastive fine tuning. Additionally, the over reliance on simply expanding context windows to accommodate more retrieved documents must be reevaluated in light of the attention degradation phenomenons observed during generation. System architectures must increasingly incorporate mechanisms for active context compression and selective attention validation to ensure that the generative model focuses exclusively on the most salient evidence [31]. Prompt engineering must also evolve from simple instruction templates to dynamic, multi step reasoning frameworks that force the model to explicitly cite the specific span of retrieved text that justifies each part of its generated response.

5.3 Limitations and Future Work

While this study provides a comprehensive overview of performance and error modalities, it is subject to certain limitations. The evaluation was primarily conducted on static datasets, which may not fully capture the dynamic, conversational nature of real world user interactions. Future research should focus on extending this analytical framework to multi turn conversational agents, where the context must be maintained and updated across sequential queries. Additionally, exploring the potential of iterative retrieval algorithms, where the language model actively dictates subsequent search queries based on the information gaps in the initially retrieved documents, represents a highly promising avenue. Ultimately, advancing the reliability of retrieval augmented generation requires a continued, rigorous commitment to identifying and understanding the nuanced ways in which these complex artificial intelligence pipelines fail.

References

Zhang, Y., Carvalho, D., & Freitas, A. (2025, July). Quasi-symbolic Semantic Geometry over Transformer-based Variational AutoEncoder. In Proceedings of the 29th Conference on Computational Natural Language Learning (pp. 12-29).

Lou, Y., Liu, J., Sheng, Y., Wang, J., Zhang, Y., & Ren, Y. (2025, March). Addressing class imbalance with probabilistic graphical models and variational inference. In 2025 5th International Conference on Artificial Intelligence and Industrial Technology Applications (AIITA) (pp. 1238-1242). IEEE.

Zeng, D., Yang, Y., Tang, Y., Zhao, L., Wang, X., Yun, D., ... & Lin, H. (2025). Shaping school for childhood myopia: the association between floor area ratio of school environment and myopia in China. British Journal of Ophthalmology, 109(1), 146-151.

Xie, C. (2026). Quantifying the Interplay Between Panic Propagation and Misinformation on Social Media Using Large Language Models. Frontiers in Artificial Intelligence Research, 3(1), 1-8.

Zhang, W., Zhang, C., Gu, C., Kou, J., Yuan, H., Fang, X., ... & Fang, Y. (2024, October). Hallucination in Large Language Models: From Mechanistic Understanding to Novel Control Frameworks. In 2024 7th International Conference on Universal Village (UV) (pp. 1-36). IEEE.

Zhang, K., Shuang, K., Yang, X., Yao, X., & Guo, J. (2023, July). What is overlap knowledge in event argument extraction? APE: A cross-datasets transfer learning model for EAE. In Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers) (pp. 393-409).

Zhang, C., Jiang, X., & Zhao, Y. (2021). Efficient instantaneous channel propagation modeling for aeronautical communications systems with compressed sensing. IEEE Transactions on Antennas and Propagation, 70(2), 1211-1220.

Du, C., Chiang, C. E., Huang, T., & Cui, Z. (2025, September). Adaptive Graph Convolution and Semantic-Guided Attention for Multimodal Risk Detection in Social Networks. In 2025 5th International Conference on Artificial Intelligence, Automation and High Performance Computing (AIAHPC) (pp. 507-512). IEEE.

Li, B., Gu, B., & Ding, Z. (2025). LLM-based Personalized Portfolio Recommender: Integrating Large Language Models and Reinforcement Learning for Intelligent Investment Strategy Optimization. arXiv preprint arXiv:2512.12922.

Liu, F., Geng, K., & Chen, F. (2025). Gone with the wind? Impacts of hurricanes on college enrollment and completion. Journal of Environmental Economics and Management, 133, 103203.

Wang, S., Yu, Y., Feldt, R., & Parthasarathy, D. (2025). Automating a complete software test process using llms: An automotive case study. arXiv preprint arXiv:2502.04008.

Tang, Y., Wang, Y., Zhang, R., & Liu, J. (2024). Linguistic steganalysis via llms: Two modes for efficient detection of strongly concealed stego. IEEE Signal Processing Letters, 32, 541-545.

Zhang, Y., Liu, J., Wang, J., Dai, L., Guo, F., & Cai, G. (2025, February). Federated learning for cross-domain data privacy: A distributed approach to secure collaboration. In 2025 8th International Symposium on Big Data and Applied Statistics (ISBDAS) (pp. 824-828). IEEE.

Vinyals, O., Fortunato, M., & Jaitly, N. (2015). Pointer networks. In Advances in Neural Information Processing Systems.

Yifan, O. U. (2018). Participating in Chinese Social Question and Answer Communities: A Case Study of Zhihu. com.

Ou, Y., de Bruijn, G. J., & Schulz, P. J. (2025). Social media as an emotional barometer: Bidirectional encoder representations from transformers–long short-term memory sentiment analysis on the evolution of public sentiments during Influenza A on Sina Weibo. Journal of Medical Internet Research, 27, e68205.

Zhang, G., Zeng, H., & Jiang, L. (2026). Uni-FinLLM: A Unified Multimodal Large Language Model with Modular Task Heads for Micro-Level Stock Prediction and Macro-Level Systemic Risk Assessment. arXiv preprint arXiv:2601.02677.

Ling, Y., & Liu, W. (2026). SR-DTMA: A Digital Twin-Driven LLM Multi-Agent Framework for Systemic Risk Simulation and Coordinated Decision-Making in Supply Chains. Journal of Computer, Signal, and System Research, 3(1), 123-132.

Tu, P., Huang, Y., Zheng, F., He, Z., Cao, L., & Shao, L. (2022, June). Guidedmix-net: Semi-supervised semantic segmentation by using labeled images as reference. In Proceedings of the AAAI conference on artificial intelligence (Vol. 36, No. 2, pp. 2379-2387).

Huang, T., Cui, Z., Du, C., & Chiang, C. E. (2025, June). CL-ISR: A Contrastive Learning and Implicit Stance Reasoning Framework for Misleading Text Detection on Social Media. In 2025 6th International Conference on Electronic Communication and Artificial Intelligence (ICECAI) (pp. 610-616). IEEE.

Shan, B., Fei, X., Shi, W., Wang, A. L., Tang, G., Liao, L., ... & Huang, C. (2024). Mctbench: Multimodal cognition towards text-rich visual scenes benchmark. arXiv preprint arXiv:2410.11538.

Cui, Z., Huang, T., Chiang, C. E., & Du, C. (2025, August). Toward verifiable misinformation detection: A multi-tool LLM agent framework. In Proceedings of the 2025 International Conference on Generative Artificial Intelligence for Business (pp. 179-185).

Fan, D., Sun, B., Dui, H., Zhong, J., Wang, Z., Ren, Y., & Wang, Z. (2022). A modified connectivity link addition strategy to improve the resilience of multiplex networks against attacks. Reliability Engineering & System Safety, 221, 108294.

Hong, J., & Ma, H. (2025). Research on an Automated Data Insight Generation Method Based on Large Language Models. Journal of Industrial Engineering and Applied Science, 3(6), 6-12.

Guo, Y., Sekiguchi, Y., Zeng, W., Ebihara, S., Owaki, D., & Hayashibe, M. (2025). Physics-informed learning framework for lower limb kinematic prediction with sparse sensors and its application in chronic stroke. IEEE Transactions on Neural Systems and Rehabilitation Engineering.

Guo, J., Shuang, K., Li, J., Wang, Z., & Liu, Y. (2022, May). Beyond the granularity: Multi-perspective dialogue collaborative selection for dialogue state tracking. In Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers) (pp. 2320-2332).

Vuruma, S. K. R., Wu, D., Gupta, S. S., Aust, L., Lookingbill, V., Henry, C., ... & Huang, M. (2024). Utilizing large language models to identify reddit users considering vaping cessation for digital interventions. arXiv preprint arXiv:2404.17607.

Li, L., Wang, Y., Fan, J., Li, J., Qin, S., Wen, Q., & Gao, F. (2025). Quantum knowledge distillation for large language models. arXiv preprint arXiv:2505.13205.

Li, K., Shuang, K., & Guo, J. (2026). Bring order to the jumbled input: Layered attention for Large Language Model based Event Argument Extraction. Engineering Applications of Artificial Intelligence, 165, 113399.

Gao, Z., Qu, Y., & Han, Y. (2025). Cross-Lingual Sponsored Search via Dual-Encoder and Graph Neural Networks for Context-Aware Query Translation in Advertising Platforms. arXiv preprint arXiv:2510.22957.

Tang, Y., Kojima, K., Gotoda, M., Nishikawa, S., Hayashi, S., Koike-Akino, T., ... & Klamkin, J. (2020). Design and Optimization of Shallow-Angle Grating Coupler for Vertical Emission from Indium Phosphide Devices.